

Product Data Sheet

Model Name: PDU 820 6 WAY UK STD AL 19"

(220~250, 50/60 Hz, 6 UK) With [Double Pole Switch and Overload Protector 13A](#)

Product Description	High-end power distribution in a compact design for IT network and server racks.
----------------------------	--

Output

Nominal Output Voltage	220~250V
------------------------	----------

Maximum Total Current Draw per Phase	13A
--------------------------------------	-----

Output Connections	6 X BS 1363 OUTLETS
--------------------	---------------------

Input

Nominal Input Voltage	220~250V
-----------------------	----------

Input Frequency	50-60 HZ
-----------------	----------

Input Connection	BS 1363 PLUG
------------------	--------------

Cord Size and Length	3C X 1.5MM ² , Length:1.8 Meter / 3 Meter / 5 Meter
----------------------	--

Maximum Input Current Per Phase	13A
---------------------------------	-----

Number of Power Cords	1
-----------------------	---

Load Capacity	3250 W MAX
---------------	------------

Overload Protection

Protection Type	Push-button Reset Overload Protector - 13A
-----------------	--

Physical

Body Type	Anodized Aluminium, Polycarbonate.
-----------	------------------------------------

Maximum Height	482 mm
----------------	--------

Maximum Width	49 mm
---------------	-------

Maximum Depth	84 mm
---------------	-------

Color	Anodized Aluminium (Silver), Black, Yellow
-------	--

Mount Type	360° Rotatable Hanger
------------	-----------------------



Features

Master Switch	Double Pole Rocker Switch (On/Off) With LED Indicator
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45 ⁰ c
Storage Temperature	-25 - 65 ⁰ c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

SASO 2815	Safety Requirements for Cord Extension Sets
BS 1363	Plugs and Socket-Outlets for Household and Similar Purposes.

Certifications



Earth Connection is Must Before Connecting to the Power Supply