

Product Data Sheet

Model Name: SAD 13 USB (ADAPTER WITH USB CHARGER)

(220~250V, 50/60 Hz, 2 X UK, 2 X USB TYPE A)

Product Description

Premium Quality Power distribution Adapter in a compact design.



Output

Nominal Output Voltage	220~250V
Maximum Total Current Draw Per Phase	13A
Output Connections	2 X BS 1363 SOCKETS
USB Spec	5V  2.1A / 2 Type A Outlets (EMC / LVD Compliance)

Input

Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	BS 1363 PLUG / FUSED
Cord Size and Length	NA
Maximum Input Current Per Phase	13A
Number of Power Cords	1
Load Capacity	3250 W MAX

Overload Protection

Protection Type	NA / FUSED 13A
-----------------	----------------

Physical

Body Type	Polypropylene (PP).
-----------	---------------------

Maximum Height	380 mm
----------------	--------

Maximum Width	49 mm
---------------	-------

Maximum Depth	54 mm
---------------	-------

Color	White
-------	-------

Weight	305 Gram
--------	----------

Features

Master Switch	Double Pole Switch (16A)
---------------	--------------------------

Fire resistance	Flame Retardant
-----------------	-----------------

Environmental

Operating Temperature	0-45°C
-----------------------	--------

Storage Temperature	-25 - 65°C
---------------------	------------

Operating Relative Humidity	0-95%
-----------------------------	-------

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

SASO 2203	Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A
-----------	---

SASO 2815	Safety Requirements for Cord Extension Sets
-----------	---

Certifications



Earth Connection is Must before connecting to the power supply