

Product Data Sheet

Model Name: SM 13 EF (WITHOUT SWITCH)

(220~250V, 50/60 Hz, 3 X UK)

Product Description Premium Quality Power distribution in a compact design.

Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw Per Phase 13A

Output Connections 3 X BS 1363 SOCKETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection BS 1363 PLUG / FUSED

Cord Size and Length 3C X 1.5MM² Length: 3 YARD / 5 YARD

Maximum Input Current Per Phase 13A

Number of Power Cords 1

Load Capacity 3250 W MAX

Overload Protection

Protection Type Push-button Reset Overload Protector - 13A

Physical

Body Type Polypropylene (PP).

Maximum Height 250 mm

Maximum Width 59 mm

Maximum Depth 29 mm

Color White

Weight 3 YARD: 495 GRAM 5 YARD: 685 GRAM



Features

Master Switch	NA
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45°C
Storage Temperature	-25 - 65°C
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

SASO 2203	Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A
SASO 2815	Safety Requirements for Cord Extension Sets

Certifications



Earth Connection is Must before connecting to the power supply