

Product Data Sheet

Model Name: PDU-1607B-C19

(220~250, 50/60 Hz, 07 C19)

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V

Maximum Total Current
Draw per Phase 16A

Output Connections 12 X IEC - C19 OUTLETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection IEC 60309 16A (2P+ ≐)

Cord Size and Length 3C X 2.5 MM², Length: 1.8 Metre / 3 Metre / 5 Metre (IEC 60227)

Maximum Input Current
Per Phase 16A

Number of Power Cords 1

Load Capacity 4000 W MAX

Overload Protection

Protection Type Double Pole MCB Breaker 16A

Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height 482 MM

Maximum Width 49 mm

Maximum Depth 84 mm

Color Anodized Aluminium, Silver/ Black,

Mount Type 1U Hanger / Non-Rotatable



Features

Master Switch	2P MCB Control
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45 ⁰ c
Storage Temperature	-25 - 65 ⁰ c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

IEC 60309	Plugs, And Socket Outlets for Industrial Purposes
IEC 60320	C13 / C19 Connectors

Certifications



Earth Connection is Must Before Connecting to the Power Supply

Actual Product May Vary from The Photo