

Product Data Sheet

Model Name: PDU-1610B-C13

(220~250, 50/60 Hz, 10 C13)

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V

Maximum Total Current
Draw per Phase 16A

Output Connections 10 X IEC - C13 OUTLETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection IEC 60309 2P+E 16A

Cord Size and Length 3C X 2.5 MM², Length: 1.8 Metre / 3 Metre / 5 Metre (IEC 60227)

Maximum Input Current
Per Phase 16A

Number of Power Cords 1

Load Capacity 4000 W MAX

Overload Protection

Protection Type Double Pole MCB Breaker 16A

Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height - mm

Maximum Width 49 mm

Maximum Depth 84 mm

Color Anodized Aluminium, Silver/ Black,

Mount Type 1U Hanger / Non-Rotatable



Features

Master Switch	2P MCB Control
---------------	----------------

Fire resistance	Flame Retardant
-----------------	-----------------

Meter

Type	Local Metered PDU
------	-------------------

Operational Voltage	220 +/- 20 % V AC, 50 / 60 Hz
---------------------	-------------------------------

Voltage Detection	176~264 V AC
-------------------	--------------

Ampere Detection	0.3 – 63 Ampere
------------------	-----------------

Environmental

Operating Temperature	0-45 ⁰ c
-----------------------	---------------------

Storage Temperature	-25 - 65 ⁰ c
---------------------	-------------------------

Operating Relative Humidity	0-95%
-----------------------------	-------

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

IEC 60309	Plugs, And Socket Outlets for Industrial Purposes
-----------	---

IEC 60320	C13 / C19 Connectors
-----------	----------------------

Certifications



Earth Connection is Must Before Connecting to the Power Supply

Actual Product May Vary from The Photo