

Product Data Sheet

Model Name: PDU-3210B-UK

(0U, Vertical PDU, 220~250V, 50/60 Hz, 10 x UK)

Product Description High-end power distribution in a compact design for IT network and server racks.

Output

Nominal Output Voltage 220~250V

Maximum Total Current
Draw per Phase 32A

Output Connections 10 X BS 1363 SOCKETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection IEC 60309 32A (2P+E)

Cord Size and Length 3C X 4MM² 1.8 METRE / 3 METRE / 5 METRES

Maximum Input Current
Per Phase 32A

Number of Power Cords 1

Load Capacity 8000 W MAX

Overload Protection

Protection Type MCB 2P 32A

Physical

Body Type Anodized Aluminium, Polycarbonate.

Maximum Height 860 MM

Maximum Width 49 mm

Maximum Depth 84 mm

Color Black, Silver Anodized

Mount Type Non-Rotatable Metal Hanger



Environmental

Operating Temperature	0-45 ⁰ c
Storage Temperature	-25 - 65 ⁰ c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

IEC 60309	Plugs, And Socket Outlets for Industrial Purposes
BS 1363	Plugs and Socket-Outlets for Household and Similar Purposes.

Certifications

