

Product Data Sheet

Model Name: PDU-3216B-C13C19

(220~250, 50/60 Hz,)

Product Description	High-end power distribution in a compact design for IT network and server racks.
Output	
Nominal Output Voltage	220~250V
Maximum Total Current Draw per Phase	32A
Output Connections	12 X C13 OUTLETS, 4 X C19 OUTLETS
Input	
Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	IEC 60309 32A (2P+ $\overline{\text{N}}$)
Cord Size and Length	3C X 4MM ² , Length: 1.8 Metre / 3 Metre /5 Metre (IEC 60227)
Maximum Input Current Per Phase	32A
Number of Power Cords	1
Load Capacity	8000 W MAX
Overload Protection	
Protection Type	Double Pole MCB C32 (32A)
Physical	
Body Type	Anodized Aluminium, Polycarbonate.
Maximum Height	- mm
Maximum Width	49 mm
Maximum Depth	84 mm
Color	Anodized Aluminium, Black, Yellow
Mount Type	360° Degree Rotatable Hanger

Features

Master Switch	2P MCB Control
---------------	----------------

Fire resistance	Flame Retardant
-----------------	-----------------

Environmental

Operating Temperature	0-45°C
-----------------------	--------

Storage Temperature	-25 - 65°C
---------------------	------------

Operating Relative Humidity	0-95%
-----------------------------	-------

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

IEC 60309	Plugs, And Socket Outlets for Industrial Purposes
-----------	---

BS 1363	Plugs and Socket-Outlets for Household and Similar Purposes.
---------	--

Certifications



Earth Connection is Must Before Connecting to the Power Supply