

Product Data Sheet

Model Name: PDU-3224B-C13C19

(220~250, 50/60 Hz, **20X C13, 4XC19 Outlets**, Vertical)

Product Description	High-end power distribution in a compact design for IT network and server racks.
----------------------------	--

Output

Nominal Output Voltage	220~250V
------------------------	----------

Maximum Total Current Draw per Phase	32A
--------------------------------------	-----

Output Connections	20 X IEC-C13 OUTLETS, 4 X IEC-C19 OUTLETS
--------------------	---

Input

Nominal Input Voltage	220~250V
-----------------------	----------

Input Frequency	50-60 HZ
-----------------	----------

Input Connection	IEC 60309 32A (2P+ $\overline{\equiv}$)
------------------	--

Cord Size and Length	3C X 4MM ² , Length: 3 Metre, / 5 Metre (IEC 60227)
----------------------	--

Maximum Input Current Per Phase	32A
---------------------------------	-----

Number of Power Cords	1
-----------------------	---

Load Capacity	8000 W MAX
---------------	------------

Overload Protection

Protection Type	MCB Breaker 32A
-----------------	-----------------

Physical

Body Type	Anodized Aluminium, Polycarbonate.
-----------	------------------------------------

Maximum Height	1400 mm
----------------	---------

Maximum Width	62 mm
---------------	-------

Maximum Depth	84 mm
---------------	-------

Color	Anodized Aluminium, Black
-------	---------------------------

Hanger Type	Non-Rotatable Metal Hanger
-------------	----------------------------



Features

Master Switch	MCB Control
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45°C
Storage Temperature	-25 - 65°C
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	3 Years Repair or Replace
-------------------	---------------------------

Standards

IEC 60309	Plugs, And Socket Outlets for Industrial Purposes
IEC 60320	C13 / C19 Connectors

Certifications



Earth Connection is Must Before Connecting to the Power Supply