

Product Data Sheet

Model Name: PDU 820 6 WAY UK STD AL 19"

(220~250, 50/60 Hz, 6 UK) With [Double Pole Switch and Overload Protector 13A](#)

Product Description	High-end power distribution in a compact design for IT network and server racks.
Output	
Nominal Output Voltage	220~250V
Maximum Total Current Draw per Phase	13A
Output Connections	6 X BS 1363 OUTLETS
Input	
Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	BS 1363 PLUG
Cord Size and Length	3C X 1.5MM ² , Length:1.8 Meter / 3 Meter / 5 Meter
Maximum Input Current Per Phase	13A
Number of Power Cords	1
Load Capacity	3250 W MAX
Overload Protection	
Protection Type	Push-button Reset Overload Protector - 13A
Physical	
Body Type	Anodized Aluminium, Polycarbonate.
Maximum Height	482 mm
Maximum Width	49 mm
Maximum Depth	84 mm
Color	Anodized Aluminium (Silver), Black, Yellow
Mount Type	360° Rotatable Hanger



Features

Master Switch Double Pole Rocker Switch (On/Off) With LED Indicator

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45^oc

Storage Temperature -25 - 65^oc

Operating Relative Humidity 0-95%

Humidity

Conformance

Standard Warranty 5 Years Repair or Replace

Standards

SASO 2815 Safety Requirements for Cord Extension Sets

BS 1363 Plugs and Socket-Outlets for Household and Similar Purposes.

Certifications



Earth Connection is Must before connecting to the power supply