

Product Data Sheet

Model Name: PDU 820 3 WAY WITH USB

(220~250V, 50/60 Hz, 3 X UK, 2 X USB)

Product Description Premium Quality Power distribution in a compact design.

Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw per Phase 13A

Output Connections 3 X BS 1363 SOCKETS; 2 X USB OUTLETS TYPE A

USB Spec 5V $\overline{\text{---}}$ 2.1A / 2 Type A Outlets

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection BS 1363 PLUG

Cord Size and Length 3C X 1.5MM², LENGTH: 3 YARD / 5 YARD

Maximum Input Current Per Phase 13A

Number of Power Cords 1

Load Capacity 3250 W MAX

Overload Protection

Protection Type Push Button Reset Overload Protector – 13A

Physical

Body Type Polyvinyl Chloride, Polycarbonate

Maximum Height 330 mm

Maximum Width 49 mm

Maximum Depth 54 mm

Color Black / Red

Packing 6 Pcs Per Carton



Features

Master Switch Double Pole Switch (On/Off)

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45^oc

Storage Temperature -25 - 65^oc

Operating Relative Humidity 0-95%

Conformance

Standard Warranty 5 Years Repair or Replace

Standards

SASO 2203 Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A

SASO 2815 Safety Requirements for Cord Extension Sets

IEC 62368-1: 2018 Safety of electronic equipment within the field of audio/video, information technology and communication technology

Certifications



Earth Connection is Must before connecting to the power supply