

Product Data Sheet

Model Name: PDU 820 4 WAY

(220~250V, 50/60 Hz, UK (4))

Product Description Premium Quality Power distribution in a compact design.

Output

Nominal Output Voltage 220~250V

Maximum Total Current
Draw per Phase 13A

Output Connections 4 X BS 1363 SOCKETS

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection BS 1363 PLUG

Cord Size and Length 3C X 1.5MM² 3 YARD / 5 YARD & 1.8M

Maximum Input Current
Per Phase 13A

Number of Power Cords 1

Load Capacity 3250 W MAX

Overload Protection

Protection Type Push-button Reset Overload Protector - 13A

Physical

Body Type Polyvinyl Chloride, Polycarbonate.

Maximum Height 340 mm

Maximum Width 49 mm

Maximum Depth 54 mm

Color Black / Red

Weight 3 YARD: 690 g 5 YARD: 890 g



Features

Master Switch	Double Pole Rocker Switch (On/Off) With LED Indicator
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45 ⁰ c
Storage Temperature	-25 - 65 ⁰ c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	5 Years Repair or Replace
-------------------	---------------------------

Standards

SASO 2203	Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A
SASO 2815	Safety Requirements for Cord Extension Sets

Certifications



Earth Connection is Must before connecting to the power supply