

Product Data Sheet

Model Name: SAD 13 USB (ADAPTER WITH USB CHARGER)

(220~250V, 50/60 Hz, 2 X UK, 2 X USB TYPE A)

Product Description

Premium Quality Power distribution Adapter in a compact design.



Output

Nominal Output Voltage 220~250V

Maximum Total Current Draw Per Phase 13A

Output Connections 2 X BS 1363 SOCKETS

USB Spec 5V $\overline{\text{---}}$ 2.1A / 2 Type A Outlets (EMC / LVD Compliance)

Input

Nominal Input Voltage 220~250V

Input Frequency 50-60 HZ

Input Connection BS 1363 PLUG / FUSED

Cord Size and Length NA

Maximum Input Current Per Phase 13A

Number of Power Cords 1

Load Capacity 3250 W MAX

Overload Protection

Protection Type NA / FUSED 13A

Physical

Body Type Polypropylene (PP).

Maximum Height 380 mm

Maximum Width 49 mm

Maximum Depth 54 mm

Color White

Weight 305 g

Features

Master Switch Double Pole Switch (16A)

Fire resistance Flame Retardant

Environmental

Operating Temperature 0-45°C

Storage Temperature -25 - 65°C

Operating Relative Humidity 0-95%

Humidity

Conformance

Standard Warranty 5 Years Repair or Replace

Standards

SASO 2203 Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A

SASO 2815 Safety Requirements for Cord Extension Sets

Certifications



Earth Connection is Must before connecting to the power supply