Product Data Sheet

Model Name: PDU 820 4 WAY WITH USB TYPE C

(220~250V, 50/60 Hz, 4 X UK, 1 X USB TYPE A, 1 X USB TYPE C)

Product Description	Premium Quality Power distribution in a compact design.



Output	
Nominal Output Voltage	220~250V
Maximum Total Current Draw per Phase	13A
Output Connections	4 X BS 1363 SOCKETS; 1 X USB OUTLETS TYPE A; 1 X USB OUTLETS TYPE C
USB Spec	5V ⎓ 2.4A / 1 Type A + 1 Type C Port / 12W MAX
Input	
Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	BS 1363 PLUG
Cord Size and Length	3C X 1.5MM^{2,} LENGTH: 3 YARD / 5 YARD
Maximum Input Current Per Phase	13A
Number of Power Cords	1
Load Capacity	3250 W MAX
Overload Protection	
Protection Type	Push Button Reset Overload Protector – 13A
Physical	
Body Type	Polyvinyl Chloride, Polycarbonate
Maximum Height	430 mm
Maximum Width	49 mm
Maximum Depth	54 mm
Color	Black / Gray

Features

Master Switch	Double Pole Switch (On/Off)
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45^{0}c
Storage Temperature	-25 - 65^{0}c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	5 Years Repair or Replace

Standards

SASO 2203	Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A
SASO 2815	Safety Requirements for Cord Extension Sets
IEC 62368-1: 2018	Safety of electronic equipment within the field of audio/video, information technology and communication technology

Certifications

Earth Connection is Must before connecting to the power supply