Product Data Sheet

Model Name: **PDU 820 4 WAY**

(220~250V, 50/60 Hz, 4 X UK)



Product Description	Premium Quality Power distribution in a compact design.
Output	
Nominal Output Voltage	220~250V
Maximum Total Current Draw per Phase	13A
Output Connections	4 X BS 1363 SOCKETS
Input	
Nominal Input Voltage	220~250V
Input Frequency	50-60 HZ
Input Connection	BS 1363 PLUG
Cord Size and Length	3C X 1.5MM^2 3 YARD / 5 YARD
Maximum Input Current Per Phase	13A
Number of Power Cords	1
Load Capacity	3250 W MAX
Overload Protection	
Protection Type	Push-button Reset Overload Protector - 13A
Physical	
Body Type	Polyvinyl Chloride, Polycarbonate.
Maximum Height	340 mm
Maximum Width	49 mm
Maximum Depth	54 mm
Color	Black / Gray

Features

Master Switch	Double Pole Rocker Switch (On/Off) With LED Indicator
Fire resistance	Flame Retardant

Environmental

Operating Temperature	0-45^{0}c
Storage Temperature	-25 - 65^{0}c
Operating Relative Humidity	0-95%

Conformance

Standard Warranty	5 Years Repair or Replace

Standards

SASO 2203	Plugs and Socket-Outlets for Household and Similar Purposes-Safety Requirements and Test Methods 250V / 13A
SASO 2815	Safety Requirements for Cord Extension Sets

Certifications